Program Name	CHP Feasibility Studies						
Program Description	Combined Heat and Power ("CHP") feasibility studies (Herein referred to as the "Program") are intended to stimulate the implementation of CHP projects by ComEd customers through enhanced visibility of the economics of site specific CHP projects. Because the economics of CHP project can vary substantially based on individual site electric and thermal loads, this Program will provide customers with the financial information needed to make an informed decision about CHP. The energy efficiency rider ("Rider EDA") will fund the CHP Feasibility Study Program. The Program will consist of the following:						
	<ul> <li>Creation of a network of CHP Program authorized developers and engineering firms that would be approved to work with ComEd customers. Program administration would create an RFP to recruit CHP developers into the network. Criteria for inclusion into the network would be based on the following:</li> </ul>						
	<ul> <li>Expertise / prior CHP project work</li> </ul>						
	<ul> <li>Ability to recruit ComEd customers</li> </ul>						
	Price						
	<ul> <li>The three phases of the Program are:</li> </ul>						
	<ul> <li>Screening phase: Review program application, verify eligibility of the customer, perform energy efficiency assessment (Smart Ideas Opportunity Assessment or equivalent)</li> </ul>						
	• <b>Feasibility phase</b> : CHP developers perform a feasibility study to include elements consistent with DCEO feasibility elements (See appendix A). Program to fund 50% of CHP developer / engineering firm fees up to \$25,000.						
	<ul> <li>Interconnection Phase: Customer and CHP developer works with ComEd distribution on the interconnection of the CHP system to the ComEd grid. Upon completion, Program to fund 50% of interconnection fees up to \$25,000.</li> </ul>						
	<ul> <li>Upon completion and operation of the CHP system, customers are eligible for incentives through the <i>Smart Ideas for Your Business</i> Custom incentive offer based on electric savings of the CHP project. Customers will submit a pre-application upon completion of the Feasibility Phase and a final application once the CHP system is operational.</li> <li>Project savings are subject to ComEd's normal EM&amp;V process that is led by independent evaluation.</li> </ul>						

Program Name	CHP Feasibility Studies						
	<ul> <li>Projects must be cost-effective on Total Resource Cost ("TRC") basis. ComEd will review the project application and, working with the customer, will determine the project's cost-effectiveness. ComEd and the customer will integrate the independent evaluator in the review process and will defer to them for final acceptance of savings methodology, savings estimates, and evaluation procedures. The parties will develop an agreed upon project review process and will make best effort to abide by this timeline.</li> </ul>						
Program Duration	June 2014 through May 2017.						
Collaborati on	ComEd will plan on offering the Program as a <i>Smart Ideas for You Business</i> program offer. ComEd will work closely with the gas companie on applicable incentives for CHP project installations. Allocation of energy savings for the projects is anticipated to be between 70% to 85% electric and 15% to 30% gas. Individual projects may vary based on the characteristics of the specific project. The energy savings split betwee electric and gas are based on the calculations from the DCEO pilot program methodology (See appendix B). We will continue to leverag opportunities from C&I education on this program and other joint gas program customer outreach and engagement activities.						
Delivery Strategy	ComEd will issue an RFP for an implementation contractor to oversee th CHP developer network, the application process, and monitor project progress as reported by customers. This process may also involv ComEd's independent evaluator, who would provide feedback of appropriate data gathering requirements and other critical aspects of project Measurement and Verification. Incentives beyond the Program and interconnection costs would be available through the traditional program infrastructure of ComEd.						
Target Market	This Program will target larger C&I customers in the ComEd servic territory, generally those customer above 1000 kW in demand.						
Marketing Strategy	The Program will rely heavily on the CHP developer network to identif and obtain participants. The program would also be promoted throug existing program channels and outreach efforts.						
Eligible Measures	CHP projects that meet the program eligibility requirements and have TRC of 1.0 or greater.						

Program Name	CHP Feasibility Studies
	<ol> <li>Newly designed and constructed Conventional CHP systems with annual fuel use efficiencies of at least 60% (HHV) with at least 20% of the system's total useful energy output in the form of useful thermal energy. These systems will have a net zero annual export of power to the grid. System efficiency is calculated as:</li> </ol>
	$CHP \ AFUE \ (HHV) = \frac{\left[Useful \ thermal \ \left(\frac{kBtu}{yr}\right) + \ Useful \ electric \ \left(\frac{kWh}{yr}\right) * 3.412 \ \left(\frac{kBtu}{kWh}\right)\right]}{F \ total \ CHP \ \left(\frac{kBtu}{yr}\right)}$
	2. Existing engine or combustion turbine systems that are not presently outfitted with heat recovery capability that can be converted to a CHP system may be eligible
Program Targets	Energy savings from this Program will be included in the C&I Incentives Program for tracking and reporting purposes. Program costs will be included in the C&I Incentives Program costs.
Appendix A – Feasibility Study Scope	<ol> <li>Table of Contents:</li> <li>Site Description:         <ul> <li>Primary business and operating schedule</li> <li>Existing energy suppliers, terms, and applicable rates</li> <li>The pressure and availability of natural gas (or other fuel to be utilized in the CHP system)</li> <li>Reasons for the CHP consideration from a host customer perspective (why are you interested in CHP)</li> <li>Facility energy use profile: a 12 to 24 month profile of electricity and fuel use, thermal loads, and costs (at a minimum please include the last 12 months of gas, electric, and steam (if applicable) bills as an appendix – not part of the 20 page limit).</li> <li>Other site description info as deemed appropriate by applicant</li> </ul> </li> <li>Energy Efficiency Status of the Site: (part of the evaluation criteria is to provide credit to those applicants that can show that the proposed site is already an energy efficient building/facility)</li> <li>Provide any data showing steps taken to improve the energy efficiency of the building/facility within the last 5 years. These might include but are not limited to upgrades in lighting/HVAC/thermal integrity; installation and operation of control systems/automated energy management systems; boiler or furnace tune-ups, steam trap maintenance/repair; or any other investments in energy efficiency.</li> </ol>

Program Name	CHP Feasibility Studies
	4. Project Description:
	<ul> <li>Narrative of CHP rationale, subsequent technology selection process</li> </ul>
	List major equipment
	<ul> <li>Prime mover – capacity, electrical efficiency, vendor cut sheets can be submitted as an appendix (not part of the 20 page limit), estimated part load performance</li> </ul>
	Heat recovery equipment
	Duct burners (if applicable)
	<ul> <li>Absorption chillers and/or desiccant dehumidifiers or other thermal recovery/use equipment being proposed as part of the project (if applicable).</li> </ul>
	Gas clean up equipment if required as part of the project
	<ul> <li>Estimated facility load profiles subsequent to CHP installation on a monthly basis</li> </ul>
	<ul> <li>CHP useful electricity production (note any parasitic power requirements)</li> </ul>
	<ul> <li>CHP provided heating/cooling (useful thermal energy production)</li> </ul>
	Grid supplied supplemental electricity requirements
	<ul> <li>Thermal loads supplied by on-site equipment (e.g., boiler and/or chiller)</li> </ul>
	<ul> <li>Estimated CHP AFUE (HHV) and related calculations on an annual basis – should use the calculation method provided in the guidelines</li> </ul>
	<ul> <li>Any interactions with the local electric utility regarding interconnection of the CHP system with the local grid.</li> </ul>
	<ul> <li>Include the type of grid being connected to (Radial or Network)</li> </ul>
	Define any estimated issues and how they will be resolved
	<ul> <li>Explain any financial impacts associated with interconnection (if applicable)</li> </ul>
	<ul> <li>One line diagrams of interconnection requirements are recommended. Any one line diagrams can be submitted as an appendix (not part of the 20 page limit).</li> </ul>
	<ul> <li>Any required interactions with the local gas utility regarding gas pressure and/or distribution lines (issues, costs, status)</li> <li>Environmental Requirements</li> </ul>

Environmental Requirements

Program Name	CHP Feasibility Studies
	Define requirements and costs
	5. Project Financials:
	<ul> <li>CHP installed cost estimates – detailed breakdown</li> </ul>
	Major equipment
	Engineering
	Design
	Construction
	Permitting
	Interconnection
	Other
	Maintenance
	• Estimated fixed and variable costs for O&M (All projects will be required to have a 5 year maintenance contract on the prime mover (at a minimum) unless otherwise waived by the DCEO. The applicant will provide justification for such waiver to be granted.
	<ul> <li>An estimate of downtime that would occur due to routine maintenance must be included</li> </ul>
	Electricity and fuel price assumptions
	<ul> <li>Electric supplier and rates before and after CHP (what specific tariffs, standby rates)</li> </ul>
	Fuel supplier and price
	Price escalation factors for grid electricity and fuel
	• Expected customer month by month savings and simple payback with and without incentives (show the effect of the project incentives on the simple payback)
	<ul> <li>Financing mechanism narrative (explain how the project will be financed)</li> </ul>
	10 year cash flow analysis
	Annual fuel and purchased power costs
	Annual O&M costs
	Annual operating savings
	<ul> <li>Assumed unit gas and electric costs &amp; pertinent escalations</li> </ul>
	IRR and NPV
	Sensitivity Analysis on simple payback based on varying
	Electric prices

Program Name	CHP Feasibility Studies
Name	<ul> <li>Fuel prices</li> <li>6. Permitting Plan – a brief description of the necessary environmental and building permits or certificates that the customer needs to obtain must be provided. A schedule of realistic permit receipt dates are to be included</li> <li>7. Metering Plan – A detailed metering plan shall be included outlining the steps that will be taken to measure system performance post-installation. After the system is installed, applicant must provide 12 months of hourly operational data demonstrating that minimum CHP AFUE was achieved. This shall be done by implementing appropriate</li> </ul>
	<ul> <li>metering as part of the system installation. Data collected should include, but is not limited to, fuel input (kBtu), useful electric energy output (kWh), useful thermal energy output (kBtu). All applicants are responsible for the monthly electronic delivery of requisite data.</li> <li>8. Project Team – include an organizational chart listing all team members, including the project manager and any subcontractors and others involved in the CHP Project, showing their roles and responsibilities. Describe the qualifications of the Applicant and/or contractor's individual and combined expertise that will enable successful completion of the CHP Project. List related projects that have been undertaken and successfully completed by the Applicant and/or contractors.</li> <li>9. Anticipated schedule – A detailed project schedule that includes design, engineering, permitting, interconnection, construction, start-up, commissioning and 12 month data collection must be provided.</li> </ul>
Appendix B – DCEO energy savings split	DCEO savings split methodology: kWh savings = (The percentage of electric Btu fuel savings) ÷ Heff CHP (Btus/kWh) Where Heff CHP = (F total CHP – F thermal CHP) ÷ useful electric output of CHP system The percentage of savings for electric and gas will vary based upon the individual project.

Program Name	CHP Feasibility Studies										
	Exam	ples of energy savin	ngs :	split for (	en	gines:					
		S fuel CHP = F grid + F thermal CHP	– F tota	I CHP							
		F grid = E CHP X H grid									
		H CHP = (F total CHP – F thermal CH S CHP Elec = S fuel CHP / H CHP	P)/E(	CHP							
		S CHP gas = S fuel CHP / 100,000 Bt	u/therm	1							
		j									
		Utility	ComE	Ed							
								SWEEP Metho	d		
				100		633		1121		3326	
	Units	Assumptions									
	kW	CHP Capacity (kW)		100		633		1121		3326	
	yrs	Measure Life (years)		20		20		20		20	
	Hrs	Operating Hours (Hrs)		6,000		6,000		6,000		6,000	
	kwh	CHP electric output (annual) CHP Gas output (annual)		600,000 40,200		3,798,000 166,800		6,726,000 259,200		19,956,000 640,200	
		w/ line losses (kWh)		666,120		4,216,540		7,467,205		22,155,151	
	11.0270	electric output in \$/yr		\$5,479		\$34,681		\$61,419		\$182,228	
		therm output in \$/yr		\$2,251		\$9,341		\$14,515		\$35,851	
		electric %		71%		79%		81%		84%	
		Gas %		29%		21%		19%		16%	
	kWh	E CHP (kWh)		600,000		3,798,000		6,726,000		19,956,000	
	2%	Parasitic Loads (kWh)		12,000		75,960		134,520		399,120	
		Total E CHP (kWh)		588,000		3,722,040		6,591,480		19,556,880	
		Grid heat rate (kBtu/kWh) (Hgrid)		11.12 6,540,171		11.12 41,399,284		11.12 73,315,320		11.12 217.526.095	
		F grid (Fg) (kBtu/yr) Usable Waste heat from CHP (kBtu/hr)		670.00		2,780.00		4,320.00		10.670.00	
	KERGATH	Thermal Utilization		80%		2,700.00		4,320.00		80%	
		Displaced thermal Eff		75%		75%		75%		75%	
		Electric Efficiency % (HHV)		27.0%		34.5%		36.8%		40.4%	
	kBtu/yr	F thermal CHP (Ft) (kBtu/yr)		4,288,000		17,792,000		27,648,000		68,288,000	
		Total CHP efficiency		69.4%		70%		69%		71%	
		Fuel Use by CHP (kBtu/hr)		1,264		6,260		10,394		28,090	
		F total CHP (Fc) (kBtu/yr) S fuel CHP [ Fq+Ft-Fc ]		7,582,222.22 3.245.949		37,561,670		62,361,717		168,539,287	
		H CHP [ (Fc-Ft)/E ]		5,245,549		21,629,614 5.21		38,601,602 5.27		<b>117,274,808</b> 5.02	
	kWh	kWh Savings (S CHP Elec)		419,033.28		3,273,628.91		5,928,596.28		19,506,948.10	
	kWh	kW Savings		415,055.20		601.35		1064.95		3159.7	
	Therms	Gas Savings (S CHP gas)		9,453.01		45,894.45		73,789.31		192,793.86	
	\$/kW	Cost/kW		\$2,900.0		\$2,737.0		\$2,289.0		\$1,822.0	
		Installation Cost	\$	290,000	\$	1,732,521	\$	2,565,969	\$	6,059,972	
	0%	Opportunity Cost	\$	-	\$	-	\$	-	\$	- 1	
	10%	Tax Credit (@10%)	\$	29,000	\$	173,252	\$	256,597	\$	605,997	
		Total 1 time cost to Cust	\$	261,000	Ś	1,559,269	\$	2,309,372		5,453,975	
	\$/kWh	Maintenance \$		\$0.024		\$0.021		\$0.019	<u> </u>	\$0.016	
	6/ Mmbtu/y	yrly maintenance	\$	14,400	\$	79,758	\$	127,794	\$	319,296	

Exam	S fuel CHP = F grid + F thermal CHP F grid = E CHP X H grid H CHP = (F total CHP – F thermal CHI S CHP Elec = S fuel CHP / H CHP	- F total CHP	or tur	bines:											
	F grid = E CHP X H grid H CHP = (F total CHP – F thermal CHP S CHP Elec = S fuel CHP / H CHP			Examples of energy savings split for turbines:											
	F grid = E CHP X H grid H CHP = (F total CHP – F thermal CHP S CHP Elec = S fuel CHP / H CHP														
	H CHP = (F total CHP – F thermal CH S CHP Elec = S fuel CHP / H CHP														
	S CHP Elec = S fuel CHP / H CHP														
	C CUD C fuel CUD / 400 000 DH	(													
	S CHP gas = S fuel CHP / 100,000 Bt	u/therm													
	Utility	ComEd													
					SWEEP Method										
		3304		7038	9950		20336								
Units	Assumptions														
	•		304	7038	005	0	20336								
							20330								
		6					6.000								
							122,016,000								
				1 - 1 - 1			4,669,200								
				46,881,526			135,462,163								
				\$385,606			\$1,114,191								
				\$115,718			\$261,475								
	electric %		3%	77%	769	6	81%								
	Gas %		27%	23%	249	6	19%								
kWh	E CHP (kWh)	19,824,	000	42,228,000	59,700,000	)	122,016,000								
2%	parasitic Loads (kWh)	396,	180	844,560	1,194,00	)	2,440,320								
	Total E CHP (kWh)	19,427,	520	41,383,440	58,506,00	)	119,575,680								
kBtu/kWh	Grid heat rate (kBtu/kWh) (Hgrid)	11	.12	11.12	11.12	2	11.12								
kBtu/yr	F grid (Fg) (kBtu/yr)	216,087,	258	460,297,252	650,747,03	3	1,330,009,223								
kBtu/hr	Usable Waste heat from CHP (kBtu/hr)	19,660	.00	34,440.00	52,360.0	)	77,820.00								
	Thermal Utilization		80%	80%	809	6	80%								
	Displaced thermal Eff		'5%	75%	759	6	75%								
	Electric Efficiency % (HHV)	23.	6%	28.91%	27.349	6	33.25%								
kBtu/yr				220,416,000			498,048,000								
							63%								
							208,681								
				the second se	the second s		1,252,085,991								
				and the second	the second s		575,971,232								
							6.18								
							75,486,782.74								
							19319.2								
			.51			1	1,094,758.38								
\$/kW							\$1,518.0								
	Installation Cost			14,639,040			30,870,048								
0%	Opportunity Cost	\$	· \$	-	\$-	\$	-								
10%	Tax Credit (@10%)	\$ 1,084,	42 \$	1,463,904	\$ 1,966,120	\$	3,087,005								
	Total 1 time cost to Cust			13,175,136			27,783,043								
\$/kWh	Maintenance \$					Ť	\$0.0093								
			326 \$			) \$	1,134,749								
	kWh 2% kBtu/kWh kBtu/yr kBtu/y	kW       CHP Capacity (kW)         yrs       Measure Life (years)         Hrs       Operating Hours (Hrs)         kwh       CHP electric output (annual)         therms       CHP Gas output (annual)         11.02%       w/ line losses (kWh)         electric output in \$/yr         therm output in \$/yr         electric %         Gas %         kWh       E CHP (kWh)         2%       parasitic Loads (kWh)         Total E CHP (kWh)         2%       parasitic Loads (kWh)         Total E CHP (kWh)         kBtu/kWh       Grid heat rate (kBtu/kWh) (Hgrid)         kBtu/kWh       Grid heat rate (kBtu/kWh) (Hgrid)         kBtu/kWh       Grid heat rate (kBtu/kWh) (Hgrid)         kBtu/kWh       Grid heat rate (kBtu/kWh)         Ulization       Displaced thermal Eff         Electric Efficiency % (HHV)       KBtu/yr         Kbtu/hr       Fuel Use by CHP (kBtu/yr)         kBtu/yr       F total CHP (Fc) (kBtu/yr)         kBtu/yr       F total CHP (Fc) (kBtu/yr)         kBtu/kWh       H CHP [(Fc-Ft)/E]         kWh       KWh Savings (S CHP Elec)         kWh       KWh Savings (S CHP gas)         \$/kW       Cost/kW	Units         Assumptions           kW         CHP Capacity (kW)         3           yrs         Measure Life (years)         6,0           hrs         Operating Hours (Hrs)         6,0           kwh         CHP electric output (annual)         19,824,0           therms         CHP Gas output (annual)         1,179,6           11.02%         w/ line losses (kWh)         22,008,6           electric output in \$/yr         \$181,           therm output in \$/yr         \$181,           therm output in \$/yr         \$66,           electric %         7           Gas %         2           kWh         E CHP (kWh)         19,824,0           2% parasitic Loads (kWh)         19,824,0           10 KBtu/xWh Grid heat rate (kBtu/kWh) (Hgrid)         11           kBtu/kWh Grid heat rate (kBtu/kWh) (Hgrid)         11           kBtu/kWh Heral Utilization         8 <td>Units         Assumptions           kW         CHP Capacity (kW)         3304           yrs         Measure Life (years)         20           Hrs         Operating Hours (Hrs)         6,000           kwh         CHP electric output (annual)         19,824,000           therms         CHP Gas output (annual)         11,179,600           11.02%         w/ line losses (kWh)         22,008,605           electric output in \$/yr         \$181,023           therm output in \$/yr         \$6000           2%         parasitic Loads (kWh)         19,824,000           2%         parasitic Loads (kWh)         19,427,520           kBtu/kWh Grid heat rate (kBtu/kWh) (Hgrid)         11.12           kBtu/kWh Grid heat rate (kBtu/kWh) (Hgrid)         11.12           kBtu/kWh Grid heat rate (kBtu/kWh)         19,620,03%           Displaced thermal Eff         75%           Electric Efficiency % (HHV)         23,96%           kBtu/yr         F total CHP (Fc) (kBtu/y</td> <td>Units         Assumptions           kW         CHP Capacity (kW)         3304         7038           yrs         Measure Life (years)         20         20           Hrs         Operating Hours (Hrs)         6,000         6,000           kW         CHP Capacity (annual)         19,824,000         42,228,000           therms         CHP Gas output (annual)         1,179,600         2,066,400           11.02%         w/ line losses (kWh)         22,008,605         46,881,526           electric output in \$/yr         \$181,023         \$3385,606           feetric %         73%         77%           Gas %         27%         23%           kWh         E CHP (kWh)         19,824,000         42,228,000           2%         parasitic Loads (kWh)         396,480         844,560           Total E CHP (kWh)         19,427,520         41,383,440           kBtu/kWh Grid heat rate (kBtu/kWh) (Hgrid)         11.12         11.12           kBtu/kWh         Usize filterioer         75%         75%           Electric Efficiency % (HHV)         23,96%         28,91%           Electric Efficiency % (HHV)         23,96%         28,91%           kBtu/yr         f thermal CHP (Ft) (kBtu/yr)</td> <td>Units         Assumptions           kW         CHP Capacity (kW)         3304         7038         995           yrs         Measure Life (years)         20         20         20         20           Hrs         Operating Hours (Hrs)         6,000         6,000         6,000         6,000           kwh         CHP electric output (annual)         19,824,000         42,228,000         59,700,000           11.02%         w/ line losses (kWh)         22,008,605         46,881,526         66,278,944           electric output in \$/yr         \$66,058         \$115,718         \$175,93           electric output in \$/yr         \$66,058         \$115,718         \$176,93           gas %         27%         223%         224,900           kWh         E CHP (kWh)         19,824,000         42,228,000         59,700,000           2% parasitic Loads (kWh)         19,824,000         42,228,000         59,700,000           2% parasitic Loads (kWh)         19,824,000         42,228,000         59,700,000           Total E CHP (kWh)         19,824,000         42,228,000         59,700,000           kBtu/Wh Grid heat rate (kBtu/khr) (Hgrid)         11.12         11.12         11.12           kBtu/Wh         F gid (kBtu/kh</td> <td>Units         Assumptions           kW         CHP Capacity (kW)         3304         7038         9950           yrs         Measure Life (years)         20         20         20           Hrs         Operating Hours (Hrs)         6,000         6,000         6,000           kwh         CHP Electric output (annual)         18,824,000         42,228,000         59,700,000           therms         CHP Gas output (annual)         1,179,600         2,066,400         3,141,600           11.0256         w/line losses (kWh)         22,006,605         46,881,526         66,278,940           electric output in \$/yr         \$66,058         \$115,718         \$1175,930           electric %         73%         77%         76%           Gas %         27%         223%         24%           kWh         E CHP (kWh)         19,824,000         42,228,000         59,700,000           2%         parasitic Loads (kWh)         19,824,000         42,228,000         59,700,000           2%         parasitic Loads (kWh)         19,824,000         42,228,000         59,700,000           2%         parasitic Loads (kWh)         11,12         11,12         11,12         11,12           kBtu/kr</td>	Units         Assumptions           kW         CHP Capacity (kW)         3304           yrs         Measure Life (years)         20           Hrs         Operating Hours (Hrs)         6,000           kwh         CHP electric output (annual)         19,824,000           therms         CHP Gas output (annual)         11,179,600           11.02%         w/ line losses (kWh)         22,008,605           electric output in \$/yr         \$181,023           therm output in \$/yr         \$6000           2%         parasitic Loads (kWh)         19,824,000           2%         parasitic Loads (kWh)         19,427,520           kBtu/kWh Grid heat rate (kBtu/kWh) (Hgrid)         11.12           kBtu/kWh Grid heat rate (kBtu/kWh) (Hgrid)         11.12           kBtu/kWh Grid heat rate (kBtu/kWh)         19,620,03%           Displaced thermal Eff         75%           Electric Efficiency % (HHV)         23,96%           kBtu/yr         F total CHP (Fc) (kBtu/y	Units         Assumptions           kW         CHP Capacity (kW)         3304         7038           yrs         Measure Life (years)         20         20           Hrs         Operating Hours (Hrs)         6,000         6,000           kW         CHP Capacity (annual)         19,824,000         42,228,000           therms         CHP Gas output (annual)         1,179,600         2,066,400           11.02%         w/ line losses (kWh)         22,008,605         46,881,526           electric output in \$/yr         \$181,023         \$3385,606           feetric %         73%         77%           Gas %         27%         23%           kWh         E CHP (kWh)         19,824,000         42,228,000           2%         parasitic Loads (kWh)         396,480         844,560           Total E CHP (kWh)         19,427,520         41,383,440           kBtu/kWh Grid heat rate (kBtu/kWh) (Hgrid)         11.12         11.12           kBtu/kWh         Usize filterioer         75%         75%           Electric Efficiency % (HHV)         23,96%         28,91%           Electric Efficiency % (HHV)         23,96%         28,91%           kBtu/yr         f thermal CHP (Ft) (kBtu/yr)	Units         Assumptions           kW         CHP Capacity (kW)         3304         7038         995           yrs         Measure Life (years)         20         20         20         20           Hrs         Operating Hours (Hrs)         6,000         6,000         6,000         6,000           kwh         CHP electric output (annual)         19,824,000         42,228,000         59,700,000           11.02%         w/ line losses (kWh)         22,008,605         46,881,526         66,278,944           electric output in \$/yr         \$66,058         \$115,718         \$175,93           electric output in \$/yr         \$66,058         \$115,718         \$176,93           gas %         27%         223%         224,900           kWh         E CHP (kWh)         19,824,000         42,228,000         59,700,000           2% parasitic Loads (kWh)         19,824,000         42,228,000         59,700,000           2% parasitic Loads (kWh)         19,824,000         42,228,000         59,700,000           Total E CHP (kWh)         19,824,000         42,228,000         59,700,000           kBtu/Wh Grid heat rate (kBtu/khr) (Hgrid)         11.12         11.12         11.12           kBtu/Wh         F gid (kBtu/kh	Units         Assumptions           kW         CHP Capacity (kW)         3304         7038         9950           yrs         Measure Life (years)         20         20         20           Hrs         Operating Hours (Hrs)         6,000         6,000         6,000           kwh         CHP Electric output (annual)         18,824,000         42,228,000         59,700,000           therms         CHP Gas output (annual)         1,179,600         2,066,400         3,141,600           11.0256         w/line losses (kWh)         22,006,605         46,881,526         66,278,940           electric output in \$/yr         \$66,058         \$115,718         \$1175,930           electric %         73%         77%         76%           Gas %         27%         223%         24%           kWh         E CHP (kWh)         19,824,000         42,228,000         59,700,000           2%         parasitic Loads (kWh)         19,824,000         42,228,000         59,700,000           2%         parasitic Loads (kWh)         19,824,000         42,228,000         59,700,000           2%         parasitic Loads (kWh)         11,12         11,12         11,12         11,12           kBtu/kr								